

LIS009409605B2

(12) United States Patent Shinoda et al.

(10) Patent No.: US 9,409,605 B2 (45) Date of Patent: Aug. 9, 2016

(54) VEHICLE BODY SIDE PART STRUCTURE

(71) Applicant: MAZDA MOTOR CORPORATION,

Hiroshima (JP)

(72) Inventors: Masafumi Shinoda, Hiroshima (JP);

Masakazu Tsuji, Higashi-Hiroshima (JP); Toshiharu Ikeda, Hiroshima (JP); Yoshikazu Nishimura, Hiroshima (JP)

(73) Assignee: MAZDA MOTOR CORPORATION,

Hiroshima (JP)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 14/414,195

(22) PCT Filed: Feb. 26, 2013

(86) PCT No.: **PCT/JP2013/001132**

§ 371 (c)(1),

(2) Date: Jan. 12, 2015

(87) PCT Pub. No.: WO2014/020784

PCT Pub. Date: Feb. 6, 2014

(65) Prior Publication Data

US 2015/0175211 A1 Jun. 25, 2015

(30) Foreign Application Priority Data

Jul. 30, 2012 (JP) 2012-168769

(51) Int. Cl.

B62D 25/00 (2006.01) **B62D 25/04** (2006.01)

(52) U.S. Cl.

CPC **B62D 25/04** (2013.01)

(58) Field of Classification Search

CPC B62D 21/157

(56) References Cited

U.S. PATENT DOCUMENTS

6,332,643	B1*	12/2001	Sukegawa B62D 25/04
			296/193.06
8,608,233	B2 *	12/2013	Mori B62D 25/04
			296/187.12
2010/0194146	Al*	8/2010	Nishimura B62D 21/157
			296/193.06
2011/0010995			Okuda et al.
2012/0153680	A1	6/2012	May et al.

FOREIGN PATENT DOCUMENTS

$^{\mathrm{CN}}$	202541645 U	11/2012
CN	202624388 U	12/2012
DE	202012000846 U1	7/2012

(Continued)

OTHER PUBLICATIONS

International Search Report; PCT/JP2013/001132; Jun. 4, 2013.

Primary Examiner — Joseph D Pape (74) Attorney, Agent, or Firm — Studebaker & Brackett PC

(57) ABSTRACT

A structure is configured such that a viewer hardly feels strangeness of color tone or texture even when paint mist is attached to a center pillar 3 during coating of a body outer plate. A panel surface of an outer panel 35 of the center pillar 3 has a protrusion in a middle in the vehicle vertical direction such that at least part of a lower portion of the panel surface projects toward the outside of the vehicle body relative to an upper portion of the panel surface. A start end HL of the protrusion is located at substantially an identical height to a door body upper edge line UL in at least a center portion in a pillar width of the pillar outer panel.

7 Claims, 13 Drawing Sheets

